



OPTION 2

1.	QUAD-LOCK REGULAR 2.25" PANEL
2.	EXTERIOR FINISH
3.	VERTICAL REINFORCEMENT AS SPECIFIED
4.	HORIZONTAL REINFORCEMENT AS SPECIFIED
5.	QUAD-LOCK TIE (6" BLUE SHOWN)
6.	SIDING PLANKS AS SPECIFIED
7.	SIDING FINISH SCREWS EXTERIOR RATED SPACED @ 12" [305mm] O.C. HOR. & VERTICAL TO MATCH SIDING SIZE
	MINIMUM SIDING LAP = 1" [25mm]
9.	QUAD-LOCK FS 2.25" PANEL

1.	QUAD-LOCK REGULAR 2.25" PANEL
2.	EXTERIOR FINISH
3.	VERTICAL REINFORCEMENT AS SPECIFIED
4.	HORIZONTAL REINFORCEMENT AS SPECIFIED
5.	QUAD-LOCK TIE (6" BLUE SHOWN)
6.	SIDING PLANKS AS SPECIFIED
7.	FASTEN FURRING STRIP TO QUAD-LOCK TIES SPACING @ 12" [305mm] O.C. VERT & HOR. WITH EXTERIOR RATED SCREWS
8.	SIDING FINISH SCREWS EXTERIOR RATED SPACED @ 12" [305mm] O.C. HOR. & VERTICAL TO MATCH SIDING SIZE
9.	MINIMUM SIDING LAP = 1" [25mm]
10.	1X2 OR 1x4 VERTICAL FURRING STRIP SPACED @ 12" O.C.



Quad-Lock Bullding Systems Ltd 7398 - 132nd Street Surrey, BC V3W 4M7

888.711.5625 - Toll Free 604.590.3111 604.590.8412 - fax

IT IS THE RESPONSIBILITY OF THE USER TO COMPLY WITH ALL APPLICABLE REGULATIONS AND BUILDING CODE REQUIREMENTS CONCERNING THE USE OF THESE PRODUCTS.

IT IS FURTHER THE RESPONSIBILITY OF THE USER TO RESEARCH AND UNDERSTAND SAFE METHODS OF USE AND HANDLING OF THESE PRODUCTS,

LAPPED SIDING FINISH DETAIL

DATE:	2009-01-21	NOT TO SCALE	
REVISION NO:	R-02	PROJECT:	
REVISION DATE:	2009-07-10	CUSTOMER:	OL COC
DRAWN BY:	Z. PROSTRAN	H.M.K. & D.J.B.	QL-606